



# Electrolux

## Modular Cooking Range Line Pasta Cooker, gas, 2 well, 10.5gal

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



Modular Cooking Range Line

Pasta Cooker, gas, 2 well, 10.5gal

**391202 (E9PCGH2MF2)**

Pasta Cooker, gas, Pair of 10.5 gallon (40 Lt) tanks, 66lb/hour capacity each, automatic starch removal, automatic low water level controls, 9 position energy controls, 316 stainless steel tanks, stainless steel cabinet & legs, 95,452 BTU

### Short Form Specification

#### Item No. \_\_\_\_\_

Pasta Cooker, gas, Pair of 10.5 gallon (40 Lt) tanks, 66lb/hour capacity each, automatic starch removal, automatic low water level controls, 9 position energy controls, 316 stainless steel tanks, stainless steel cabinet & legs, 95,452 BTU



APPROVAL: \_\_\_\_\_

### Main Features

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- High efficiency 32 kW burners in stainless steel with flame failure device and power settings for each well, located below the well.
- Water basin in 316-L type Stainless steel.
- Water basin is seamlessly welded into the top of the appliance.
- Provided with integrated drip zone on which baskets can be placed for draining purposes.
- Automatic starch removal function during cooking: improved water quality over time.
- Automatic low-water level shut-off: no accidental over-heating.
- Easy-to-use control panel with gas cock and piezo ignition.
- All major compartments located in front of unit for ease of maintenance.
- Continuous water filling regulated through a manual water tap.
- Large drain with manual ball-valve for fast emptying of well.
- Thermocouple device for added safety.
- IPX5 water resistance certification.
- The special design of the control knob system guarantees against water infiltration.
- One piece pressed 0.07" (2mm) work top in Stainless Steel.
- Unit delivered with four 2" (50mm) legs in stainless steel as standard (all round Stainless steel kick plates as option).
- 10.5gal (40lt) water basins.

### Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

### Included Accessories

- 2 of Door for open base cupboard PNC 206350

### Optional Accessories

- Junction sealing kit PNC 206086 ☐
- Air-draft diverter, 5 29/32" diam. PNC 206132 ☐
- Matching ring for flue condenser, 5 29/32" diam. PNC 206133 ☐



Electrolux

Modular Cooking Range Line  
Pasta Cooker, gas, 2 well, 10.5gal

Electrolux Professional, Inc.

[www.electroluxusa.com/professional](http://www.electroluxusa.com/professional)

10200 David Taylor Drive, Charlotte, NC 28262 • Telephone Number: 866-449-4200 • Fax Number: 704-547-7401



# Electrolux

## Modular Cooking Range Line Pasta Cooker, gas, 2 well, 10.5gal


- Kit 4 wheels - 2 swivelling with brake - it is mandatory to install base support and wheels PNC 206135 ☐
- Flanged feet kit PNC 206136 ☐
- Frontal kicking strip for concrete installation 800 mm PNC 206148 ☐
- Frontal kicking strip for concrete installation, 39 3/8" wide PNC 206150 ☐
- Frontal kicking strip for concrete installation, 47 1/4" wide PNC 206151 ☐
- Frontal kicking strip for concrete installation, 63" wide PNC 206152 ☐
- Frontal kicking strip, 31 1/2" wide PNC 206176 ☐
- Frontal kicking strip, 39 3/8" wide PNC 206177 ☐
- Frontal kicking strip, 47 1/4" wide PNC 206178 ☐
- Frontal kicking strip, 63" wide PNC 206179 ☐
- 2 side kicking strips PNC 206180 ☐
- 2 panels for service duct for single installation PNC 206181 ☐
- Lid and lid holder for 10.5 gallon (40 Lt) pasta cooker PNC 206190 ☐
- 2 panels for service duct for back to back installation PNC 206202 ☐
- 4 feet for concrete installation PNC 206210 ☐
- Set of three ergonomic baskets for 10.5 gallon (40 Lt) pasta cooker. To be used with support PNC 206238 PNC 206233 ☐
- Single ergonomic basket for 10.5 gallon (40 Lt) pasta cooker. To be used with support PNC 206238 PNC 206237 ☐
- Support for 10.5 gallon (40 Lt) pasta cooker square baskets PNC 206238 ☐
- Flue condenser for 1 module, 150 mm diameter PNC 206246 ☐
- Chimney upstand, 800mm PNC 206304 ☐
- - NOT TRANSLATED - PNC 206308 ☐
- - NOT TRANSLATED - PNC 206309 ☐
- Energy saving device for pasta cookers PNC 206344 ☐
- Door for open base cupboard PNC 206350 ☐
- - NOT TRANSLATED - PNC 206353 ☐
- Base Support Assembly, 48" (1200mm) wide, for feet/wheels PNC 206368 ☐
- Base Support Assembly, 64" (1600mm) wide, for feet/wheels PNC 206369 ☐
- Base Support Assembly, 80" (2000mm) wide, for feet/wheels PNC 206370 ☐
- Base support for feet or wheels (lateral) for pastacookers (900XP) PNC 206372 ☐
- Rear paneling - 800mm PNC 206374 ☐
- Rear paneling - 1000mm PNC 206375 ☐
- Rear paneling - 1200mm PNC 206376 ☐
- - NOT TRANSLATED - PNC 206395 ☐
- CHIMNEY GRID NET, 400MM-700&900LINE PNC 206400 ☐
- 2 square baskets, left and right, for 10.5 gallon pasta cooker. 6 baskets can be fitted in 900 pasta cooker. To be used with support PNC 206238 PNC 206433 ☐
- Side handrail-right/left hand PNC 216044 ☐
- FRONTAL HANDRAIL 800 MM PNC 216047 ☐
- FRONTAL HANDRAIL 1200 MM PNC 216049 ☐
- FRONTAL HANDRAIL 1600 MM PNC 216050 ☐
- 2 side covering panels for free standing appliances PNC 216134 ☐
- Large handrail - portioning shelf, W=31 1/2" PNC 216186 ☐
- Set of three baskets (11" x 6") for 10.5 gallon (40 Lt) pasta cooker PNC 927210 ☐
- Pair of baskets (11" x 9") for 10.5 gallon (40 Lt) pasta cooker PNC 927211 ☐
- Set of three portion baskets for 10.5 gallon (40 Lt) pasta cooker - round (requires support for baskets PNC 927219) PNC 927212 ☐
- Set of six single-portion baskets for 10.5 gallon (40 Lt) pasta cooker - round - requires support rack (PNC 927219 or 960644) PNC 927213 ☐
- Basket (11" x 18") for 10.5 gallon (40 Lt) pasta cooker PNC 927216 ☐
- Support for 10.5 gallon (40 Lt) pasta cooker round basket PNC 927219 ☐
- Top support for set of six pasta cooker round baskets. An alternative to 927219 when set of six round baskets used PNC 960644 ☐




# Electrolux

## Modular Cooking Range Line Pasta Cooker, gas, 2 well, 10.5gal

Front




Top



**D = Drain**  
**EI = Electrical connection**  
**EQ = Equipotential screw**  
**G = Gas connection**  
**WI = Water inlet**

Side



### Electric

#### Supply voltage:

**391202 (E9PCGH2MF2)** 208/120 V/1 ph/60 Hz

Convertible to: 120V/1Ph/60Hz

**Rated amps:** 0.3A (0.6A/120V)

**Total Watts:** 0.05 kW

### Gas

**Gas Power:** 106000 Btu/hr (31 kW)

**Gas Type Option:** LPG; Natural Gas

**Gas Inlet:** 3/4"

**Natural gas - Pressure:** 4" w.c. (10 mbar)

**LPG Gas Pressure:** 10" w.c. (25 mbar)

### Water:

**Drain "D":** 1"

**Incoming Cold/hot Water line size:** 3/4"

**Total hardness:** 5-50 ppm

**Electrolux** recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

### Key Information:

<b>Usable well dimensions (width):</b>	300 mm
<b>Usable well dimensions (height):</b>	260 mm
<b>Usable well dimensions (depth):</b>	520 mm
<b>Well Capacity (MAX):</b>	40 lt MAX
<b>Net weight:</b>	115 kg
<b>Shipping weight:</b>	140 kg
<b>Shipping height:</b>	1120 mm
<b>Shipping width:</b>	1020 mm
<b>Shipping depth:</b>	860 mm
<b>Shipping volume:</b>	0.98 m <sup>3</sup>

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.